

## Separation Devices by Frost – Overview of all Types

	NTE-296 S	NTE-296 S2	NTE-350 S	NTE-350 S2	NTE-200 P	NTE-200 P2	NTE-200 L	NTE-200 L2
<b>Drive</b>	electro-mechanical	electro-mechanical	electro-mechanical	electro-mechanical	pneumatic	pneumatic	manually	manually
<b>Performance</b>	230V/50-60Hz 115V/50-60Hz	230V/50-60Hz 115V/50-60Hz	230V/50-60Hz 115V/50-60Hz	230V/50-60Hz 115V/50-60Hz	6 bar	6 bar	-	-
<b>Activation</b>	footswitch	footswitch	footswitch	footswitch	footswitch	footswitch	hand lever	hand lever
<b>Separation Length</b>	up to 300 mm	up to 300 mm	up to 350 mm	up to 350 mm	up to 200 mm	up to 200 mm	up to 200 mm	up to 200 mm
<b>Tool Opening</b>	16-fold (0.4 to 1.5 mm)	16-fold (0.4 to 1.5 mm)	16-fold (0.4 to 1.5 mm)	16-fold (0.4 to 1.5 mm)	up to 1,5 mm	up to 1,5 mm	up to 1,5 mm	up to 1,5 mm
<b>Adjustment</b>	reproducible	reproducible	reproducible	reproducible	manual with adjusting screw	manual with adjusting screw	manual with adjusting screw	manual with adjusting screw
<b>Tabletop &amp; Footrest</b>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Selectable cutting tools</b>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<b>Attachment of cutting tools</b>	flexible with groove	screw fastening	flexible with groove	screw fastening	flexible with groove	screw fastening	flexible with groove	screw fastening